www.carriercca.com

Carrier®
turn to the experts™

Carrier

turn to the experts℠

Carrier One

Puron
the environmentally sound refrigerant

Golden
anti-corrosion treated condenser

- Auto Restart function
- Active Carbon filter
- LED display
- Turbo & Sleep mode

TECHNICAL SPECIFICATIONS

Indoor Unit Model Number			42KHA009L	42KHA012L	42KHA018L	42KHA024L
Outdoor Unit Model Number			38KHA009LP	38KHA012LP-1	38KHA018LP	38KHA024LP
Nominal Capacity			9000	12000	18000	24000
Power supply		V-Hz-Ph	208-230V~ 60Hz, 1Ph	208-230V~ 60Hz, 1Ph	208-230V~ 60Hz, 1Ph	208-230V~ 60Hz, 1Ph
Rating Performance	Nominal Capacity	Btu/h	9000	12000	18000	24000
	Input	W	940	1256	1880	2490
	Current	A	4.2	5.7	8.5	11.4
	EER	W/W	2.81	2.80	2.81	2.82
Max. input consumption		W	1100	1850	2500	3500
Max. input current		A	5.5	9.0	12.9	17.0
Indoor unit	Dimension (W×D×H)	mm	715x195x285	681x285x434	958x213x302	1038x235x325
	Packing (W×D×H)	mm	780x285x360	795x345x495	1035x305x380	1120x405x310
	Net/Gross weight	kg	7.0 / 9.0	8.1/9.9	10.5 / 13.5	12.5 / 16.0
Outdoor unit	Dimension(WxDxH)	mm	681x285x434	700×275×550	770×300×555	845×363×702
	Packing(WxDxH)	mm	795x370x495	815×350×615	910×380×615	985×435×760
	Net/Gross weight	kg	20.5 / 24.0	23.7/25.6	32.0 / 36.5	40.5 / 46.0
Indoor noise level (Hi/Med/Lo)		dB(A)	38/34/28	39/33/28	44/39/33	47/42/36
Outdoor noise level		dB(A)	52	53	58	60
Refrigerant type/ Quantity	Type		R410A	R410A	R410A	R410A
	Factory charge	kg	0.40	0.46	0.56	0.91
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ9.52(1/4”/3/8”)	Φ6.35/Φ9.52(1/4”/3/8”)	Φ6.35/Φ12.7(1/4”/1/2”)	Φ9.52/Φ15.9(3/8”/5/8”)
	Max. pipe length	m	20	20	25	25
	Max. difference in level	m	8	8	10	10
Controller (Wireless)			RG56	RG56	RG56	RG56
Operation temperature	Space temperature range	℃	18~32	18~32	18~32	18~32
	Ambient temperature range	℃	18~43	18~43	18~43	18~43

Authorized Distributor: